

## **Container Handler**

Used Container Handler Vallejo - Container handlers, also known as cargo ships and container ships transport their load in a large intermodal container. Containerization is the shipping method that utilizes commercial freight transport to carry seagoing cargo in non-bulk sizes. The capacity of these specialty ships is equal to twenty-foot loads. Typical loads range with a mixture of 20-foot and 40-foot containers. Approximately ninety percent of non-bulk cargo across the globe is transported by container ships. Container handlers are one of the biggest vessels sailing and are the main rival for oil tankers on the ocean. There are two main categories for dry cargo which are break-bulk and bulk cargo. Grain and coal are bulk cargo, typically transported in their raw format inside the ships hull, free from packages. Break-bulk cargo items normally consist of manufactured goods that are transported in packages. Before the 1950s when containerization hadn't been invented yet, break-bulk materials were loaded, secured and unattached one piece at a time in a very time-consuming process. When the cargo was grouped into containers, there were approximately 1000-3000 cubic feet of cargo that can be simultaneously moved after each unit has been standardized and secured. Break-bulk cargo shipping has greatly increased overall efficiency. It is estimated that shipping time has been reduced by eighty-four percent and costs have been reduced by approximately thirty-five percent. In 2001, over ninety percent of non-bulk materials were recorded as being transported in containers. The first cargo ships were born in the 1940s as redesigns from World War II tankers. Container ships do not rely on individual hatches, holds and dividers that are part of regular cargo ships. The typical container ship's hull is a basically a large warehouse that is divided by vertical guide rails into cells. These cells have been designed to transport the cargo in containers. Most cargo ships are designed from steel but additional materials such as plywood, fiberglass and wood are used. Designed to be completely transferred to and from trains, semi-trailers, trucks, coastal carriers and more, there is a variety of container types that are categorized by their function and size. The entire shipping industry has been revolutionized by containerization, although, it did not start out in the easiest manner. Initially, ports, railway companies and shippers were concerned regarding the extensive costs that came with constructing infrastructure, ports and railways required to accommodate the cargo ships and transporting items with rail and roads. Numerous trade unions were concerned that containers would affect port jobs and manual labor associated with cargo handling for dock and port workers. There was a decade of legal battles prior to the container ships starting international service. By 1966, after the first container liner service began from Rotterdam, Netherlands to the USA, cargo shipping was transformed. Loading and unloading of cargo ships has been reduced to a few hours instead of the days it used to take traditional cargo vessels. Shipping times have been shortened in between ports extensively along with labor finances. It only takes 3 weeks to have materials delivered from Europe to India as opposed to the months it used to require. Overall, there is less damaged cargo thanks to less physical handling and reduced cargo shifting due to properly securing loads. Before shipping, containers are closed and only opened after they arrive at their new location to prevent theft and damage. Container ships have reduced shipping time and lessened shipping expenses, resulting in enhanced international trade growth. Sealed factory containers now carry cargo that used to arrive in barrels, cartons, crates, bags and bales. Scanning machines work with computers to trace the product code on the contents. Technological advancements have enabled this accurate tracking system to be precise within fifteen minutes on arrival of a two-week voyage. This has helped with guaranteed delivery and manufacturing times. Raw materials show up in sealed containers from factories in under an hour prior to being used in the manufacturing industry; resulting in fewer inventory expenses and greater accuracy. The shipping companies supply the exporters with boxes for loading products. They are delivered into the docks by rail or road or a combination of both to be loaded onto container ships. Containerization has streamlined the process of loading by reducing the number of workers and hours it takes to fit cargo into their holds. Cranes are used in the shipping industry or

on the pier to organize containers. After the hull has been fully loaded, additional containers can be attached to the deck. Efficiency has been one of the main design elements for cargo ships. Break-bulk ships may carry containers. However, cargo holds that have been dedicated to container ships have been carefully built to speed up the loading and unloading process and designed to keep containers secure while traveling the ocean. There is a sophisticated hatch design to allow openings from the main deck to reach the cargo hold locations. These openings are situated along the entire cargo hold breadth, surrounded by a raised steel structure called the hatch coaming. There are hatch covers located on top of the hatch coamings. Wooden boards and tarps initially covered the hatches and held the battens secure until the 50s. Hatch covers are made of secure metal plates and cranes are used to lift them on and off of the ship. There are other hatch models that rely on articulated mechanisms that use strong hydraulic rams for opening and closing. Cell guides are a necessary component in cargo ship design. Attached to the cargo hold in the ship, cell guides are vertical pieces of metal that help organize the cargo. They work by guiding containers into particular rows while loading and help to support items during travel. Since the design of the container ship utilizes cell guides in such abundance, the UN Conference on Trade and Development relies on them to separate traditional break-bulk cargo ships and container ships. There is a system used in cargo plans consisting of three dimensions to outline a container's position aboard the ship. The first coordinate is the bay which begins at the front of the ship and increases aft. The tier is the second coordinate, with the initial tier staring at the bottom of the cargo holds with the second, tier situated on top of the first and continuing on. The third coordinate is found in the third row. Rows found on the port side of the ship exhibit even numbers and those located on the starboard side are given odd numbers. Rows that are located along the ships' center are designated lower numbers and they increase for locations found further from the center. Container handlers carry 20, 40 and 45 foot containers. The biggest sizes only fit above the deck. The forty-foot containers comprise most of the load or roughly 90% of container shipping. Roughly 90% of the freight in the world is delivered via container shipping. Approximately eighty-percent of global freight is shipped via forty-foot containers.